

# **APPLICATION INSTRUCTIONS**

APPLY TO FRONT-FACE OF WHEELS ONLY\*

#### **01. CLEAN THE WHEELS**

**Items:** Warm Water | Dish Soap | Microfiber Cloth (not included) Wash and completely dry the wheel surfaces to be coated.

## **02. REMOVE FINE DUST / FINGERPRINTS**

**Items:** Blue Application Pad (I of 2 included) | Rubbing Alcohol (included) Mix a solution of 50% rubbing alcohol and 50% water. Use one blue application pad to thoroughly wipe down the front-face of each wheel with this solution. Allow surfaces to completely dry.

### **03. APPLY COATING**

Items: Blue Application Pad (2 of 2 included) | Ceramic Coating (included)

Use ceramic coating sparingly. Apply a small amount of ceramic coating to one side of the clean application pad and coat half the wheel by wiping spoke by spoke. Allow 30-60 seconds of "flash time" while watching for a slight change in appearance. Buff the coating with the backside of the application pad. Repeat on the second half (uncoated portion) of the wheel. A single application pad should be adequate for four wheels.

### 04. WAIT TO CURE

After application, allow wheels to sit for 1 hour. Keep wheels dry for 24 hours. Do NOT wash wheels for 1 week.

\*20ml bottle adequately covers the face of four standard-size wheels without excessively deep lips. Excessively large wheels or wheels with deep lips may require two bottles. Additional bottles will be needed to cover wheel barrels and/or backsides.